

TECHNICAL DATA SHEET

BRICK & SLASTO DRESSING



GENERAL DESCRIPTION:

A solvent based clear gloss acrylic UV and abrasion resistant penetrating clear brick sealer to enhance and protect face brick, slasto and natural stone for interior and exterior use.

USES:

Suitably prepared new/weathered or previously coated with face brick, slasto and cladded natural stone after suitable preparation.

FEATURES & BENEFITS:

- UV Resistant
- Enhances the natural beauty of the coated surface
- Alkali and abrasion resistant
- Excellent penetration & adhesion properties
- Rapid drying

TECHNICAL INFORMATION	
1. BRICK & SLASTO DRESSING	
PHYSICAL FORM	Thin transparent liquid
COLOUR	Clear, pale golden brown
FINISH	Glossy, Smooth
SPREADING RATE	Approximately 9 - 11 m ² /ℓ per application at 20-25µm DFT = 100-110µm WFT depending on surface porosity, profile, and application method
POLYMER TYPE	Modified alkyd resin
	Recommended film WFT:100-110µm and DFT: 20-25µm
DENSITY	Density at 23°C Approx.: 0.85±0.05 kg/L
SOLIDS	Solids Content: By weight Approx. 29±2%, By volume: Approx. 22±2%
VISCOSITY	Viscosity at 23°C: Approx. FC4 – 25-35 Sec
FILLERS	None
PIGMENTS	None
DRYING PROPERTIES	Surface or touch-dry: within 1 hour
RECOATING TIME	4h depending on conditions and film build
FLASH POINT	42°C (Contains flammable solvent)
PACKAGING	1ℓ & 5ℓ
MIXING	Stir the contents thoroughly with a flat paddle before use
THINNING	Use a minimum quantity of mineral turpentine if required
CLEANING	Clean all tools (brushes & rollers) while wet with Mineral Turpentine after use
APPLICATION METHOD	Brush and airless spray: <ul style="list-style-type: none"> - Non- porous surfaces: Ready for use apply one coat Fired Earth Brick & Slasto Dressing. - Porous surfaces: Thin 10 parts Fired Earth Brick & Slasto Dressing to 1-part Mineral Turpentine. Apply 2-3 coats, allowing 4 hours drying time between coats. - Exceptionally porous surfaces: Thin 1 parts Fired Earth Brick & Slasto Dressing to 1-part Mineral Turpentine. Apply 2-3 coat, allowing 4 hours drying time between coats

**B.DS.086
FB SERIES****DO NOT PAINT**

IF THE TEMPERATURE IS BELOW 10°C OR ABOVE 35°C

IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 15%)

IF IT IS RAINING OR RAIN IS FORECAST

BEFORE 9H00 AND AFTER 16H00 IN THE WINTER

NEW AND WEATHERED UNCOATED BRICK, SLASTO OR STONE SURFACES:**NEW:**

Ensure surfaces are dry (15% moisture maximum), in sound condition. Remove all wax polish, oil, clean and free from any contaminants such as dust, dirt, salt, and grease with Fired Earth All- In-One Surface Cleaner (Grease, Dirt, Mould & Fungi Cleaner). Allow to dry. Remove all cement stains and excess mortar with Fired Earth Mortar-Strip.

WEATHERED, SLASTO OR STONE SURFACES:

Remove all loose slivers, powdery material. Brush off loose dust. Remove all wax polish, oil, clean and free from any contaminants such as dust, dirt, salt, and grease with Fired Earth All- In-One Surface Cleaner (Grease, Dirt, Mould & Fungi Cleaner). Allow to dry. Remove all cement stains and excess mortar with Fired Earth Mortar-Strip. Ensure surfaces are dry (15% moisture maximum), in sound condition.

PREVIOUSLY COATED SURFACES WITH BRICK OR SLASTO DRESSING:

Remove all wax polish, oil, clean and free from any contaminants such as dust, dirt, salt, and grease with Fired Earth All- In-One Surface Cleaner (Grease, Dirt, Mould & Fungi Cleaner). Remove all suborn wax polish, oil cement or previously non sealed brick sealer stains and excess mortar with Fired Earth Mortar-Strip. Remove all cement stains and excess mortar with Fired Earth Mortar-Strip. Ensure surfaces are dry (15% moisture maximum), in sound condition.

IMPORTANT:

The above application is a guide, additional coats may be required depending on the type of substrate and surface porosity, for the best protection and decorative appearance.

Do not apply over other types of brick dressings or varnishes unless the compatibility has been established beforehand or stripped with Fired Earth Paint Strip (where non conspicuous test area is established beforehand). Then continue with the preparation for PREVIOUSLY COATED SURFACES WITH BRICK OR SLASTO DRESSING before applying Fired Earth Brick & Slasto Dressing. Avoid applications to hot surfaces as this may cause bubbling. Roller application not recommended as this may cause bubbling.

HEALTH & SAFETY ADVICE

The product contains a flammable solvent. Precaution must be taken to prevent naked flames coming in contact with vapours (i.e. smoking must be prohibited). Solvents may also cause narcotic effects if the vapour concentration is too high: always ensure adequate ventilation (do not use solvent based paints in a poorly ventilated or closed space). Avoid contact with skin, eyes, mouth etc. Wear protective clothing, goggles & gloves. If body contact is made, rinse off immediately. Wash product off skin before it has dried using soap and water.

DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.