



**B.DS.052
BW SERIES**

TECHNICAL DATA SHEET

KITCHENS & BATHROOMS



GENERAL DESCRIPTION:

Fired Earth Kitchens & Bathrooms paint is a high quality pigmented hygienic water based paint. The product is formulated with silver biocides that protects the paint film surface and inhibits the growth of microorganisms. It has a subtle sheen finish with excellent adhesion, stain resistance and washability. It is also mould, water and steam resistant in high humidity areas. Application can be for either primed new work, or previously sound painted areas.

USES:

INTERIOR, New or previously painted, masonry plaster, gypsum, concrete, fibre cement and brick surfaces after suitable preparation. Ideal for kitchen & Bathrooms where a hard-wearing finish is required.

FEATURES & BENEFITS:

- Lead free
- Excellent wet and dry adhesion properties
- Rapid drying – 2 Coats can be applied in one day
- Water based
- Alkali, steam, water & mould resistant
- Easily cleanable or washable
- Environmentally friendly
- Specially formulated to resist mildew growth on the paint film

TECHNICAL INFORMATION	
1. KITCHENS & BATHROOMS	
PHYSICAL FORM	A low odour medium viscosity liquid paint
COLOUR	White only
FINISH	Smooth subtle sheen finish
SPREADING RATE	6 - 8 m ² / l per coat. (Two coats recommended)
POLYMER TYPE	Acrylic co-polymer
FILLERS	Non-toxic fine particle sized extenders
PIGMENTS	Non-toxic weather and light resistant types only
DRYING PROPERTIES	Surface or touch-dry: within 30 minutes
RECOATING TIME	2 - 4 hours depending on conditions and film build
FLASH POINT	Non-flammable (water based product)
PACKAGING	2.5L
THINNING	Not recommended. The product is supplied ready for use. May be sprayed using Airless Spray Equipment
CLEANING	Do not allow the product to dry on equipment. Equipment is readily cleaned using water
APPLICATION METHOD	Supplied ready-for-use. Apply using good roller designed for PVA paint products

DO NOT PAINT
IF THE TEMPERATURE IS BELOW 10°C OR ABOVE 35°C
IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 15%)
IF IT IS RAINING OR RAIN IS FORECAST
BEFORE 9H00 AND AFTER 16H00 IN THE WINTER



**B.DS.052
BW SERIES**

APPLICATION DETAILS

New Surfaces

Surfaces must be thoroughly clean, dry and in sound condition before painting.

Concrete / Cement: Apply one coat of Fired Earth all-in-one™ Plaster Primer, followed by two coats of Fired Earth Kitchens & Bathrooms paint.

Asbestos / Fibre Cement: Apply one coat of Fired Earth all-in-one™ Plaster Primer, followed by two coats of Fired Earth Kitchens & Bathrooms paint.

Gypsum Plaster: Apply one coat of Bonding Liquid or Solvent-based Plaster Primer followed by two coats of Fired Earth Kitchens & Bathrooms paint.

Previously Painted Surfaces

Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Apply one coat of Fired Earth all-in-one™ Plaster Primer, followed by two coats of Fired Earth Kitchens & Bathrooms paint. Ensure that the surface is correctly prepared before painting.

HEALTH & SAFETY

Keep paint away from children. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.