

TECHNICAL DATA SHEET

NEW COAT



GENERAL DESCRIPTION:

Fired Earth New Coat Acrylic is a quality decorative acrylic paint for interior use with excellent hiding power. May be used as a filler coating under medium quality acrylic paints on interior walls and ceilings over suitably prepared surfaces.

USES:

Interior use, new or previously painted masonry, plaster, gypsum, concrete, fibre cement and brick surfaces after suitable preparation.

FEATURES & BENEFITS:

- Low VOC & Lead free
- Alkali resistant
- Superior dry opacity
- Good adhesion properties
- Rapid drying-2 coats in one day
- Easy to apply
- Water clean up

TECHNICAL INFORMATION

1. NEW COAT

PHYSICAL FORM	Non-flammable viscous liquid containing pigments and extenders. May have slight ammonia odour
COLOUR	White
FINISH	Smooth, Matt
SPREADING RATE	Approximately 6 - 8 m ² per litre per application
POLYMER TYPE	Alkali-resistant acrylic copolymer latex
PIGMENTS & FILLERS	Weather and light resistant types only
DRYING PROPERTIES	Surface or touch-dry: within 1hour
RECOATING TIME	2-4 hours depending on conditions during drying
FLASH POINT	Not flammable in liquid form
PACKAGING	5L & 20L
THINNING	Not recommended, but if required to reduce viscosity add a minimum quantity of WATER. Excessive dilution degrades the quality of the product. (NB: DO NOT add solvent-based thinners such as turpentine or lacquer thinners)
CLEANING	Do not allow the product to dry on equipment. Equipment is readily cleaned using (Some detergent may be added to water to facilitate clean up)
APPLICATION METHOD	Apply this product with a quality paint brush or suitable paint roller for smooth, rough or coarse surfaces

DO NOT PAINT

IF THE TEMPERATURE IS BELOW 10 ⁰ C OR ABOVE 35 ⁰ C
IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 15%)
IF IT IS RAINING OR RAIN IS FORECAST
BEFORE 9H00 AND AFTER 16H00 IN THE WINTER

**B.DS.061
FB SERIES**

NEW SURFACES

- a) Concrete / Cement plaster: Apply 1 coat Fired Earth Nano-Tech Plaster Primer (Water Based) followed 2 coats Fired Earth New Coat Acrylic.
- b) Fibre Cement: Apply 1 coat Fired Earth Nano-Tech Plaster Primer (WB) followed 2 coats Fired Earth New Coat Acrylic.
- c) Gypsum Plaster/ Rhinolite: Apply 1 coat Fired Earth Nano-Tech Plaster Primer (WB) or Fired Earth Nano-Tech Bonding Liquid (WB) followed 2 coats Fired Earth New Coat Acrylic.

PREVIOUSLY PAINTED SURFACES

Thoroughly clean and prepare surfaces by removing all dirt, grease, mould, grime and flaking paint before starting to paint. Apply 1 coat Fired Earth Nano-Tech Plaster Primer (WB) and 2 coats of Fired Earth New Coat Acrylic leaving at least 2-4 hours between coats.

Please note Fired Earth New Coat Acrylic must under no circumstances be used as a substitute for Fired Earth Nano-Tech Plaster Primer (Water Based).

HEALTH & SAFETY

Keep paint away from children. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.