

SAFETY DATA SHEET

Date issued 10/07/2020

BW SERIES: FE SOFT WAX

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Code	BW SERIES	Product Name	FE SOFT WAX
Recommended use	A paint or paint constituent product		
Company Name	Promac Paints (Pty) Ltd		
Address	PO Box 75351 Lynwood Ridge 0040 -		
Telephone	012 804 7305		
Facsimile	012 804 2040		
Emergency Contact	-		
Contact	- T. Patel		
Contact number	- 012 804 7305		

SECTION 2. HAZARDS IDENTIFICATION

Overall Nature Hazardous goods
Classification reference SANS10234 (1272/2008/EC) :
Classification of the substance or mixture

- (H226) Flammable liquids, Hazard Category 3
- (H304) Aspiration hazard, Hazard Category 1

GHS label elements, including precautionary statements

Signal word Danger
Pictograms



Hazard and Precautionary Statements

	Hazard Statements
(H226)	Flammable liquid and vapour
(H304)	May be fatal if swallowed and enters airways
	Precautionary Statements
	Prevention Statements
(P210)	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
(P233)	Keep container tightly closed.
(P240)	Ground/bond container and receiving equipment. – if the explosive is electrostatically sensitive.
(P241)	Use explosion-proof electrical/ventilating/lighting/.../ equipment.
(P242)	Use only non-sparking tools.
(P243)	Take precautionary measures against static discharge.
(P280)	Wear protective gloves/protective clothing/eye protection/face protection.
	Response Statements
(P301+P310)	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
(P303+P361+P353)	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
(P331)	Do NOT induce vomiting.
(P370+P378)	In case of fire: Use powder/... for extinction.
	Storage Statements
(P403+P235)	Store in a well-ventilated place. Keep cool.
(P405)	Store locked up.
	Disposal Statements
(P501)	Dispose of contents/container in accordance with local/regional/ national/international regulations in accordance with local/regional/ national/international regulation

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS


Product type : Mixture **Generic name :** PAINT PRODUCT

CAS No. : Not applicable **EU Index No :** Not applicable **UN No :** 1263

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

Name	% m/m	EC Label	CAS Number	EC Index
1 WHITE SPIRIT (WS3) Xn	50.47 %	265-191-7	064742-88-7	649-405-00-X
2 Other non-hazardous items	49.53 %			

Classification reference SANS10234 (1272/2008/EC) of constituents

ref above table	Hazard Code	Pictogram
1 Item 1 above	H304	 -
ref above table	Classification	
1 Item 1 above	Asp. Tox. 1	

SECTION 4. FIRST AID MEASURES

Inhalation	Move to fresh air. In case of discomfort seek medical attention.
Skin	Use hand cleaner/soap & water. Remove contaminated clothing. If any discomfort get medical attention
Eyes	Rinse immediately with plenty of water. Seek medical advice if symptoms persist.
Ingestion	DO NOT INDUCE VOMITING. Get immediate medical attention.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media :

Foam. CO2. Dry powder. Fog to cool and control. Do NOT use water jets.

Specific hazards arising from the chemical :

Containers can burst in a fire. Can form explosive vapour/air mixture. Static discharge hazard!
Flammable with toxic fumes.
Cool containers in case of fire.

Special protective actions for fire-fighters :

Suitable extinguishing media : Foam, dry agent
Substance reacts violently/is explosive
For fires use breathing apparatus. If no fire, breathing apparatus not essential
Prevent, by any means available, spillage from entering drains or water courses

SECTION 6. ACCIDENTAL RELEASE MEASURES

Contain & collect. Keep out of drains and sewers
Wear protective equipment (see Section 8). Keep unprotected persons away.
Do not allow product to reach sewage system or any water course.
Remove ignition sources and provide sufficient ventilation

SECTION 7. HANDLING AND STORAGE

Storage :

Store separately from : explosives, toxic gases, oxidising substances, organic peroxides, poisonous (toxic) substances, infectious substances (biohazards),
No open flames. No smoking.
Keep containers cool. Avoid free fall of liquid - use earthing.
Subject to local bylaws

Handling :

Ensure good ventilation/exhaustion at the workplace
Do not spray on a naked flame or any incandescent material
Eating, drinking and smoking in work areas is prohibited
Wash hands after use
Remove contaminated clothing and protective equipment before entering eating areas

Inhalation	In case of insufficient ventilation, use suitable respiratory protection.
Skin	Use barrier cream and impervious gloves.
Eyes	Use face shield & goggles or full face respirator/hood. Avoid direct contact.
Ingestion	Observe the rules of hygiene. Wash before eating or drinking.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

Name	CAS Number	TWA OEL	TWA OEL	STOEL		
STOEL	OEL	Vap.Press.	(mg/m3)	(mg/m3)	(ppm)	Type (mmHg)
FE SOFT WAX	-	-	-	-	-	-
Components :	Not applicable					
WHITE SPIRIT (WS3) Xn	064742-88-7	575	100	720	125	RL

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

OEL Type : Mixture

Maintain air concentrations below occupational exposure standards, using engineering controls as necessary

Appropriate hand protection and protective clothing must always be used

Keep away from foodstuffs, beverages and feed

Wash hands before breaks and at the end of work

Personal protective equipment :

Skin PPE : Overall and impervious gloves (eg nitrile rubber)

Respiratory PPE : Air purifying respirator (eg cartridge type)

Eye PPE : Faceshield or solvent resistant goggles

HMIS Rating (USA) 2 - 3 - 0 - I (Health-Flam-Reactivity-PPE)

SAPMA Rating 2-H-E PPE : Gloves, Respirator and Eye protection



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Property	Value
Appearance	Viscous liquid
Odour	Pungent
pH	not available
Boiling point	>100°C
Melting point	not available
Flash point	>23°C
Explosive prop	not available
Oxidizing prop	not available
Vapour pressure	not available
Density	0.815 Kg/L
Water solubility	--
Fat solubility	--
Partition coefficient	not available
Viscosity	Thick paste
Vapour density	not available
Evaporation rate	not available
Autoignition temperature	not available
L.E.L.	not available
U.E.L.	not available
% non volatile	not available

SECTION 10. STABILITY AND REACTIVITY

Stable under normal conditions

Could generate static - USE EARTHING

No reaction with fire-fighting water

Keep away from : explosives, toxic gases, oxidising substances, organic peroxides, poisonous (toxic) substances, infectious substances (biohazards),

SECTION 11. TOXICOLOGICAL INFORMATION

Name	CAS Number	LD50 Oral	LD50 Skin	LC50 Inhal(gas)	LC50 Inhal(mist)
		mg/kg	mg/kg	ppmV	mg/lt
FE SOFT WAX	-	>500	-	-	-
Components :	Not applicable				
WHITE SPIRIT (WS3) Xn	064742-88-7	>5000 mg (Rat)			

Inhalation	Irritating, narcotic. Can affect CNS.
Skin	Irritating, risk of dermatitis.
Eyes	Irritating.
Ingestion	Harmful. May cause lung damage if swallowed.

SECTION 12. ECOLOGICAL INFORMATION

May have short term environmental effects. Contain, monitor & remove
 Aquatic toxicity : No further relevant information available
 Persistence and degradability : No further relevant information available.
 Bioaccumulative potential : No further relevant information available.
 Mobility in soil : No further relevant information available.

No available ecological data of ingredients :

SECTION 13. DISPOSAL INFORMATION

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

SECTION 14. TRANSPORT INFORMATION

UN Number	1263		
Shipping Name	PAINT PRODUCT		
IMO Class	3	Packing Group	III
Action Code	127		
HazChem	3[Y]		



SECTION 15. REGULATORY INFORMATION

Classification reference SANS10234 (1272/2008/EC) :
Classification of the substance or mixture
 (H226) Flammable liquids, Hazard Category 3
 (H304) Aspiration hazard, Hazard Category 1

SECTION 16. OTHER INFORMATION

TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGES.
 IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.
 HMIS Rating (USA) : 2 - 3 - 0 - I (Health-Flam-Reactivity-PPE)

Hazard (H) phrases associated with components

H304 : May be fatal if swallowed and enters airways

Abbreviations

- Code : Abbreviation : Meaning
- Xn : : harmful
- ==== : :
- : : Associated pictogram code shown in brackets
- H304 : Asp. Tox. 1 : (GHS08) Aspiration hazard, Hazard Category 1
- ==== : :
- GHS01 : : Exploding bomb
- GHS02 : : Flame
- GHS03 : : Flame over circle
- GHS04 : : Gas cylinder
- GHS05 : : Corrosion
- GHS06 : : Skull and crossbones
- GHS07 : : Exclamation mark
- GHS08 : : Health hazard
- GHS09 : : Environment
- : %m/m : Percent by mass
- : ATE : Acute Toxicity Estimate
- : CAS : Chemical Abstracts Service
- : CHIP : Chemicals (Hazard Information and Packaging for supply)
- : CLP : Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
- : CNS : Central Nervous System

: DIN : Standard of the German Institute for Standardisation
: DOT : Department of Transport
: EC : European Community
: EC50 : Effective Concentration (Median) for 50% of the response under test
: ECB : European Chemicals Bureau
: ECHA : European Chemicals Agency, Helsinki (http://echa.europa.eu/home_en.asp)
: EEC : European Economic Community
: EINECS : European Inventory of Existing Chemical Substances
: ELINCS : European List of Notified Chemical Substances
: GHS : Globally Harmonized System of Classification and Labelling of Chemicals
: HMIS : Hazardous Materials Information System (USA only)
: IATA : International Air Transport Association
: IMDG : International Maritime Dangerous Goods Code
: IMO : International Maritime Organization
: INS : Guidance on Identification and Naming of Substances under REACH, ECHA, 2007
: ISO : International Standards Organisation
: L.E.L. : Lower explosive limit
: LD50/LC50 : Median (50%) lethal dose/concentration
: mg/m3 : Milligrams per cubic meter
: MSDS : Material safety data sheet
: n.a. : Not available
: NC : No Classification
: No : Number
: OEL : Occupational exposure limit
: OEL-CL : Occupational exposure limit - control limit
: OEL-RL : Occupational exposure limit - recommended limit
: OHS Act : Occupational Health and Safety Act
: P statement : Precautionary statement
: PPE : Personal protective equipment
: ppm : Parts per million
: REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals
: RTDG : Regulations on the Transport of Dangerous Goods. Generic term that covers all modal transport regulations (ADR, RID, ADN, IMDG and ITDG)
: SABS : South African Bureau of Standards
: SANS : South African National Standards
: SAPMA : South African Paint Manufacturers Association
: SARA 313 : Toxic Release Inventory Reporting SRA Section 3
: SDS : Safety Data Sheet
: STOEL : Short-term occupational exposure limit
: STOT-RE : Specific Target Organ Toxicity - Repeated Exposure
: STOT-SE : Specific Target Organ Toxicity - Single Exposure
: TDG : Transport of Dangerous Goods
: TSCA : Toxic Substance Control Act (USA only)
: TWA : Time weighted average
: U.E.L. : Upper explosive limit
: UN : United Nations
: WHMIS : Workplace Hazardous Materials Information Systems (Canada only)
: ===== :

This SDS conforms with General Administrative Regulations of 6 Sept.1996 (SANS11014:2010/ISO11014:2009)
OELs derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42)
SAPMA Rating - South African Paint Manufacturers Association Guide to Health Hazards (SABS ARP 006:1991)
All information is given in good faith but without guarantee in respect of accuracy.
No responsibility is accepted for errors or omissions or the consequences thereof.

(Date of issue : 10/07/2020 Date of analysis : 10/07/2020)