

**B.DS.011**  
**BW SERIES**



**FIRED  
EARTH™**

## TECHNICAL DATA SHEET

### ULTIMATE



#### GENERAL DESCRIPTION:

A high quality, smooth, pure acrylic, medium sheen Acrylic Wall coating is a durable, high quality technologically advanced, pure acrylic paint with a luxurious medium sheen finish. It has been specially formulated with improved and enhanced benefits for maximised protection.

#### USES:

All interior and exterior on new or previously painted surfaces where a high quality medium pure acrylic sheen finish is required.

#### FEATURES & BENEFITS:

- Lead free
- Low VOC
- Washable & stain resistant
- Flexible
- All weather & UV resistant
- Easy to use

### TECHNICAL INFORMATION

#### 1. ULTIMATE

PHYSICAL FORM	A low odour medium viscosity liquid paint
COLOUR	White and Standard Colours
FINISH	Smooth, medium sheen
SPREADING RATE	Approximately 6 - 8 m <sup>2</sup> per litre per application
POLYMER TYPE	New Technology Pure Acrylic incorporating Nanotechnology
FILLERS	Non-toxic fine particle sized extenders
PIGMENTS	Non-toxic weather and light resistant types only
DRYING PROPERTIES	Surface or touch-dry: within 1 hour
RECOATING TIME	2 – 4 hours depending on conditions during drying
FLASH POINT	Not flammable in liquid form
PACKAGING	5L & 20L
THINNING	Not recommended, but if required to reduce viscosity add a minimum quantity of WATER. Excessive dilution degrades the quality of the product. (NB: DO NOT add solvent-based thinners such as mineral turpentine)
CLEANING	Do not allow the product to dry on equipment. Equipment is readily cleaned using water. (Some detergent may be added to water to facilitate clean up)
APPLICATION METHOD	Supplied ready-for-use. Apply using a very good quality roller

#### DO NOT PAINT

IF THE TEMPERATURE IS BELOW 10°C OR ABOVE 35°C
IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 15%)
IF IT IS RAINING OR RAIN IS FORECAST
BEFORE 9H00 AND AFTER 16H00 IN THE WINTER



**FIRED  
EARTH™**

**B.DS.011  
BW SERIES**

**APPLICATION DETAILS**

**New Surfaces:**

Surfaces must be thoroughly clean, dry and in sound condition before painting.

**Concrete / Cement:**

Apply one coat of Fired Earth all-in-one™ Plaster Primer, followed by two coats of ULTIMATE Mid Sheen Pure **Acrylic Wall Coating:**  
Asbestos / Fibre Cement: Apply one coat of Fired Earth all-in-one™ Plaster Primer, followed by two coats of ULTIMATE Mid Sheen Pure Acrylic Wall Coating.

**Gypsum Plaster:**

Apply one coat of Bonding Liquid or Solvent-based Plaster Primer followed by two coats of ULTIMATE Mid Sheen Pure Acrylic Wall Coating.

**Previously Painted Surfaces:**

Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Apply one coat of Fired Earth all-in-one™ Plaster Primer, followed by two coats of ULTIMATE Mid Sheen Pure Acrylic Wall Coating. Ensure that the surface is correctly prepared before painting.

**Mixing**

Stir the contents thoroughly before use.

**HEALTH & SAFETY**

Keep paint away from children. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

**DISCLAIMER ADVICE**

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.