

SAFETY DATA SHEET

Date of issued 12/01/2016

**BW SERIES: FE WOODWORKS INTERIOR & EXTERIOR WB
SEALER****SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product Code	BW SERIES	Product Name	FE WOODWORKS INTERIOR & EXTERIOR WB
SEALER			
Recommended use	A paint or paint constituent product		
Company Name	Promac Paints (Pty) Ltd		
Address	PO Box 75351 Lynwood Ridge 0040 -		
Telephone	012 804 7305		
Facsimile	012 804 2040		
Emergency Contact	- M.Soooramoney- 012 8047305		

SECTION 2. HAZARDS IDENTIFICATION

Overall Nature EC Classification : Not classified as hazardous
Classification reference SANS10234 (1272/2008/EC) :
Classification of the substance or mixture

(H316) Skin corrosion/irritation, Hazard Category 3

GHS label elements, including precautionary statements

Signal word Warning
Pictograms None

Hazard and Precautionary Statements

Hazard Statements

Causes mild skin irritation

Precautionary Statements

Response Statements

If skin irritation occurs: Get medical advice/ attention.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product type : Mixture	Generic name :	UN No : Not applicable
CAS No. : Not applicable	EU Index No : Not applicable	
HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS		
Name FE WOODWORKS INTERIOR & EXTERIOR WB SEALER	% m/m	EC Labels CAS Number EC Index
TRIMETHYL-PENTADIOL- MONOISOBUTYRATE		
1,2- PROPYLENE GLYCOL	<1.9 %	025265-77-4 n/q
	<1.8 %	000057-55-6 o

Classification reference SANS10234 (1272/2008/EC) :
EC Index Classification | Hazard Code | Note |

SECTION 4. FIRST AID MEASURES

Inhalation	Move to fresh air.
Skin	Always wash after being in contact with chemical substances.
Eyes	Rinse with plenty of water. Seek medical advice if symptoms persist.
Ingestion	Give plenty of water/milk. Induce vomiting if patient conscious. Get medical advice.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media :

Specific hazards arising from the chemical :

No direct explosion hazard expected.

Dried residues - combustible with toxic fumes.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Contain & collect. Caution - Can make floors slippery.

Wear protective equipment (see Section 8). Keep unprotected persons away.

Do not allow product to reach sewage system or any water course.

Remove ignition sources and provide sufficient ventilation

SECTION 7. HANDLING AND STORAGE

Storage :

Alkaline - corrosive. Caution with contact with non-ferrous metals.

Handling :

Ensure good ventilation/exhaustion at the workplace

Do not spray on a naked flame or any incandescent material

Eating, drinking and smoking in work areas is prohibited

Wash hands after use

Remove contaminated clothing and protective equipment before entering eating areas

Inhalation

In case of insufficient ventilation, use suitable respiratory protection.

Skin

Observe the rules of hygiene.

Wash before eating, drinking or smoking.

Eyes

Avoid direct contact. Never touch eyes with dirty hands or gloves.

Ingestion

Observe the rules of hygiene. Wash before eating, drinking or smoking.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

Name	CAS Number	TWA OEL (mg/m3)	TWA OEL (ppm)	STOEL (mg/m3)	STOEL (ppm)	OEL Type	Vap.Press. (mmHg)
FE WOODWORKS INTERIOR & EXTERIOR WB SEALER	-	Not applicable					
Components :							
TRIMETHYL-PENTADIOL- MONOISOBUTYRATE	025265-77-4	400	100			RL	
1,2- PROPYLENE GLYCOL	000057-55-6	470	220			VAP	0.22

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

OEL Type : Mixture

Maintain air concentrations below occupational exposure standards, using engineering controls as necessary

Appropriate hand protection and protective clothing must always be used

Keep away from foodstuffs, beverages and feed

Wash hands before breaks and at the end of work

Personal protective equipment :

Skin PPE : Overall and impervious gloves (eg nitrile rubber)

Respiratory PPE : Air purifying respirator (eg cartridge type)

Eye PPE : Faceshield or solvent resistant goggles

HMIS Rating (USA) 1 - 0 - 0 - I (Health-Flam-Reactivity-PPE)

SAPMA Rating 3-H-E PPE : Gloves, Respirator and Eye protection



SPRAYBOOTH

Spraybooth Type Spraybooth complying with National Standards

Skin PPE Nitrile Gloves

Eyes PPE Faceshield or solvent resistant goggles

Respiratory Protection Air supplied full facepiece or head covering respirator suitable for organic vapours/particulates

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Property	Value
Appearance	Water based emulsion

Odour	Slight
pH	8.5
Boiling point	>100°C
Melting point	not available
Flash point	n/a°C
Explosive prop	not available
Oxidizing prop	not available
Vapour pressure	not available
Density	0.95-1.05Kg/L
Water solubility	miscible
Fat solubility	Oil : insoluble
Partition coefficient	not available
Viscosity	70-75KU
Vapour density	not available
Evaporation rate	not available
Autoignition temperature	not available
L.E.L.	not available
U.E.L.	not available
% non volatile	25-30%

SECTION 10. STABILITY AND REACTIVITY

Stable under normal conditions
No reaction with fire-fighting water

SECTION 11. TOXICOLOGICAL INFORMATION

Name	CAS Number	LD50 Oral	LD50 Skin	LC50 Inhal(gas)	LC50 Inhal(mist)
WOODWORKS INTERIOR & EXTERIOR WB SEALER - mg/lit	-	-	mg/kg	mg/kg	ppmV
Not applicable	41667 ATEoral	125000 ATEdermal	333333 ATEgas	-	-
Components :	-----	-----	-----	-----	-----
TRIMETHYL-PENTADIOL- MONOISOBUTYRATE	025265-77-4	3200 mg (Rat)	16ml/Gg		
1,2- PROPYLENE GLYCOL	000057-55-6	21000+ mg (Rat)			

Inhalation	Possible traces of free monomers. Can be irritating.
Skin	Direct contact to be avoided.
Eyes	Can cause damage.
Ingestion	Irritating and nauseating.

SECTION 12. ECOLOGICAL INFORMATION

May have short term environmental effects. Contain, monitor & remove
Aquatic toxicity : No further relevant information available
Persistence and degradability : No further relevant information available.
Bioaccumulative potential : No further relevant information available.
Mobility in soil : No further relevant information available.

Available ecological data of ingredients :

Name	CAS Number	Envirodata
1,2- PROPYLENE GLYCOL	000057-55-6	LOW FISH TOXICITY

SECTION 13. DISPOSAL INFORMATION

Can be eliminated from sewage/effluent by chemical flocculation.
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

SECTION 14. TRANSPORT INFORMATION

UN Number Not applicable Not classified as dangerous for transport

SECTION 15. REGULATORY INFORMATION

Classification reference SANS10234 (1272/2008/EC) :

Classification of the substance or mixture
(H316) Skin corrosion/irritation, Hazard Category 3

SECTION 16. OTHER INFORMATION

IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.
HMIS Rating (USA) : 1 - 0 - 0 - I (Health-Flam-Reactivity-PPE)

Abbreviations

Code : Abbreviation : Meaning

===== : :

: : Associated pictogram code shown in brackets

===== : :

: %m/m : Percent by mass

: ATE : Acute Toxicity Estimate

: CAS : Chemical Abstracts Service

: CHIP : Chemicals (Hazard Information and Packaging for supply)

: CLP : Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

: CNS : Central Nervous System

: DIN : Standard of the German Institute for Standardisation

: DOT : Department of Transport

: EC : European Community

: EC50 : Effective Concentration (Median) for 50% of the response under test

: ECB : European Chemicals Bureau

: ECHA : European Chemicals Agency, Helsinki (http://echa.europa.eu/home_en.asp)

: EEC : European Economic Community

: EINECS : European Inventory of Existing Chemical Substances

: ELINCS : European List of Notified Chemical Substances

: GHS : Globally Harmonized System of Classification and Labelling of Chemicals

: HMIS : Hazardous Materials Information System (USA only)

: IATA : International Air Transport Association

: IMDG : International Maritime Dangerous Goods Code

: IMO : International Maritime Organization

: INS : Guidance on Identification and Naming of Substances under REACH, ECHA, 2007

: ISO : International Standards Organisation

: L.E.L. : Lower explosive limit

: LD50/LC50 : Median (50%) lethal dose/concentration

: mg/m3 : Milligrams per cubic meter

: MSDS : Material safety data sheet

: n.a. : Not available

: NC : No Classification

: No : Number

: OEL : Occupational exposure limit

: OEL-CL : Occupational exposure limit - control limit

: OEL-RL : Occupational exposure limit - recommended limit

: OHS Act : Occupational Health and Safety Act

: P statement : Precautionary statement

: PPE : Personal protective equipment

: ppm : Parts per million

: REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals

: RTDG : Regulations on the Transport of Dangerous Goods. Generic term that covers all modal transport regulations (ADR, RID, ADN, IMDG and ITDG)

: SABS : South African Bureau of Standards

: SANS : South African National Standards

: SAPMA : South African Paint Manufacturers Association

: SARA 313 : Toxic Release Inventory Reporting SRA Section 3

: SDS : Safety Data Sheet

: STOEL : Short-term occupational exposure limit

: STOT-RE : Specific Target Organ Toxicity - Repeated Exposure

: STOT-SE : Specific Target Organ Toxicity - Single Exposure

: TDG : Transport of Dangerous Goods

: TSCA : Toxic Substance Control Act (USA only)

: TWA : Time weighted average

: U.E.L. : Upper explosive limit

: UN : United Nations

: WHMIS : Workplace Hazardous Materials Information Systems (Canada only)

===== : :

This SDS conforms with General Administrative Regulations of 6 Sept.1996 (SANS11014:2010/ISO11014:2009)

OELs derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42)

SAPMA Rating - South African Paint Manufacturers Association Guide to Health Hazards (SABS ARP 006:1991)

All information is given in good faith but without guarantee in respect of accuracy.

No responsibility is accepted for errors or omissions or the consequences thereof.

(Date of issue : 12/01/2016 Date of analysis : 12/01/2016)