



WATERPROOFING RANGE RUBBERISED BITUMEN

Fired Earth Damp X RBE Rubberised Bitumen Emulsion is a single component rubberised - bitumen based waterproofing and sealing paint.

FEATURES & BENEFITS

- Dark brown colour
- The cured film is non-toxic
- Asbestos free
- Seamless / joint free
- Excellent adhesion to most surfaces

USES

Fired Earth Damp X RBE is used to waterproof roofs and parapets as well as sealing of ponds, dams, etc. It is applied for tanking and waterproofing structures. Can also be used in place of Hydro Flex, impregnating liquid in the reinforcing membrane waterproofing system, by applying one saturator coat, onto a sound surface followed by one finishing coat. Can also act as a curing agent when applied to fresh concrete. May be applied to damp, but not waterlogged surfaces.

PRODUCT INFORMATION - PHYSICAL & TECHNICAL INFORMATION

PHYSICAL FORM:	Dark Brown / Black viscous Liquid
COLOURS:	Dries Black
FINISH:	Low sheen
SPREADING RATE:	4 - 6m ² per litre per application
POLYMER TYPE:	Rubberised Bitumen Emulsion
DRYING PROPERTIES:	Touch dry 1 hour
RECOATING TIME:	Over coating time 2 - 4 hours-depending on temperature conditions @ 23°C
FLASH POINT:	N/A - Waterborne Product
PACKAGING SIZES:	5ℓ & 20ℓ
THINNING:	Not recommended, but if required to reduce viscosity add a 10% maximum quantity of Water. Excessive dilution degrades the quality of the product
CLEANING:	Do not allow the product to dry on equipment. Equipment is readily cleaned using water or when CLEANING dry mineral turpentine, lacquer thinners or cleaning solvent
APPLICATION METHOD:	Supplied ready-for-use, cold applied. Stir well then apply using a brush or roller. First coat does not need to be diluted when applied to porous surfaces. Apply at least 3 coats for pond or dam linings. Leave each coat to cure for at least 4h before applying the next coat. Leave the complete coating system to age for at least 10-14 days before filling the pond or dam. Use the reinforcing membrane for cracked or uneven surfaces. Make sure that the fabric is thoroughly impregnated with RBE Super Cold Rubberised Bitumen to ensure optimum waterproofing properties

Masstores (Pty) Ltd.

Registration No: 1991/006805/07

Address: 16 Peltier Dr, Sunninghill, Sandton, 2157

P.O Box: Private Bag x4, Sunninghill, 2157

E-mail: info@massmart.co.za

Web: www.builders.co.za

Tel: +27 (10) 594 8000

Fax: +27 (11) 797 0400

Exclusive to



PHYSICAL FORM: Dark Brown / Black viscous Liquid

DO NOT PAINT IF

IF THE TEMPERATURE IS BELOW 100C OR ABOVE 350C
IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 15%)
IF IT IS RAINING OR RAIN IS FORECAST
BEFORE 9H00 AND AFTER 16H00 IN THE WINTER

SURFACE PREPARATION

Surfaces must be dry, clean, sound and free of any loose material (e.g., peeling paint, rust etc).

- a) Metal surfaces must be primed with a suitable Multi-metal primer.
- b) Masonry surfaces must be sealed with Bonding Liquid (a good quality bonding liquid) to ensure the surface is sound before applying RBE Super Cold Rubberised Bitumen Emulsion.

NOTES:

- Holes/Gaps/Cracks >5mm: Make good all holes, gaps and cracks with the appropriate fillers to ensure a sound, firm surface for good adhesion of primers and sealers.
- Do not paint if rain is expected.
- Do not use RBE Super Cold Rubberised Bitumen Emulsion under tiles.

HEALTH & SAFETY

Keep paint away from children and animals. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.

Exclusive to

