



## TEXTURED RANGE GRANULAR COAT

**Fired Earth Granular Coat** paint is a rough textured acrylic coating with a rare granular effect and natural finish. **Fired Earth Granular Coat** paint has a ground matt appearance once dry.

### FEATURES & BENEFITS

- Granular sand, coarse textured matt finish
- Durable & long lasting protective coating
- Easy to apply
- Fills hairline cracks and disguises minor surface defects and repaired areas
- Water clean up
- Lead content, less than 90 ppm

### USES

#### INTERIOR / EXTERIOR

For application to suitably primed new cement plaster, concrete, fibre-cement, gypsum plaster, porous brickwork and various types of building boards.

### PRODUCT INFORMATION - PHYSICAL & TECHNICAL INFORMATION

<b>PHYSICAL FORM:</b>	Textured paste-like fluid. May have an ammonia odour
<b>COLOURS:</b>	Selected standard colours
<b>FINISH:</b>	Grainy rough texture with a matt finish
<b>TYPICAL SPREADING RATE:</b>	This product will cover approximately 1 to 3 m <sup>2</sup> / litre per coat depending on the type of substrate and surface porosity
<b>POLYMER TYPE:</b>	Modified flexible, water-resistant acrylic
<b>FILLERS:</b>	Quartz, mica and acid-resistant non-toxic extenders
<b>PIGMENTS:</b>	Lightfast and alkali-resistant types only
<b>DRYING PROPERTIES:</b>	Touch-dry: 2 hours
<b>RECOATING TIME:</b>	Over coating time: 4-6 hours
<b>FLASH POINT:</b>	Not flammable in liquid form
<b>PACKAGING SIZES:</b>	5ℓ & 20ℓ
<b>THINNING:</b>	No thinning required, product is supplied ready for use
<b>CLEANING:</b>	Clean all tools while wet with water after use
<b>APPLICATION METHOD:</b>	Cut and apply Granular in small areas at a time approximately 2 to 4 m <sup>2</sup> , keeping a wet edge apply Granular using a long pile wool or quality synthetic roller and work uninterruptedly from corner to corner of the wall on the first coat. On the second coat the pattern can be varied from a coarse rolled texture to a more brushed pattern using a moist 150 mm block brush. If the brushed finish is desired drag the block brush from top to bottom whilst the paint is wet and as you progress painting small areas from start to finish. Allow 4-6 hours drying time between coats Two coats are required. This paint should not be touched up. Not suitable for spraying

#### Masstores (Pty) Ltd.

Registration No: 1991/006805/07

Address: 16 Peltier Dr, Sunninghill, Sandton, 2157

P.O Box: Private Bag x4, Sunninghill, 2157

E-mail: info@massmart.co.za

Web: www.builders.co.za

Tel: +27 (10) 594 8000

Fax: +27 (11) 797 0400

Exclusive to



### DO NOT PAINT IF

IF THE TEMPERATURE IS BELOW 100C OR ABOVE 350C  
IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 15%)  
IF IT IS RAINING OR RAIN IS FORECAST  
BEFORE 9H00 AND AFTER 16H00 IN THE WINTER

### SURFACE PREPARATION

Surfaces must be thoroughly clean, dry and in sound condition before painting.

SURFACES	PRIMER / SYSTEM
Concrete / Cement, Fibre Cement, Gypsum plaster	Apply two coats of Fired Earth Plaster Primer Water Based Nano-Tech followed by two coats of <b>Fired Earth Granular Coat</b> .

### PREVIOUSLY PAINTED SURFACES

Ensure that the surface is correctly prepared before painting. Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Apply one coat of Fired Earth Plaster Primer, prior to applying two coats of **Fired Earth Granular Coat**.

### MIXING

Stir the contents thoroughly with a flat paddle before use.

### IMPORTANT

Ensure to have enough paint to complete the job. Should different batches be used, it is advised to mix different batches together before commencing application for uniformity, especially of colour and even finish. Do not apply using mohair or enamel rollers. Not suitable for spraying. Plan to complete a wall from corner to corner in one application. This paint should not be touched up.

### HEALTH & SAFETY

Keep paint away from children and animals. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

### DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.

Exclusive to

