



**B.DS.029
BW SERIES**

TECHNICAL DATA SHEET

NON-DRIP ENAMEL



GENERAL DESCRIPTION:

Fired Earth Non-Drip Enamel is a multi-purpose water-based enamel paint ideal for kitchens and bathroom walls, ceilings, trim, window and door frames, gutters and downpipes.

USES:

New or previously painted surfaces where a high-quality tough silky satin smooth finish is required. Recommended for all suitably primed, plaster, fibre cement, concrete, wood and metal surfaces. Ideal for kitchens and bathrooms and recommended as a trim paint.

FEATURES & BENEFITS:

- Drip free
- Non-yellowing
- Hard wearing
- Washable & stain resistant
- Good opacity & film build

TECHNICAL INFORMATION

1. NON-DRIP ENAMEL

PHYSICAL FORM	Non-flammable viscous liquid containing non-toxic pigments and extenders. May have a slight ammonia odour
COLOUR	White
FINISH	Silky Satin smooth
SPREADING RATE	Approximately 6 - 8 m ² / l per application
POLYMER TYPE	Alkali-resistant Pure Acrylic
FILLERS	Non-toxic extenders
PIGMENTS	Weather resistant types only
DRYING PROPERTIES	Surface or touch-dry: within 2 hours
RECOATING TIME	2 - 4h depending on conditions and film build
FLASH POINT	Not flammable in liquid form
PACKAGING	1L & 5L
THINNING	Not recommended, but if required to reduce viscosity add a minimum quantity of WATER. Excessive dilution degrades the quality of the product
CLEANING	Do not allow the product to dry on equipment. Equipment is readily cleaned using (Some detergent may be added to water to facilitate clean up)
APPLICATION METHOD	Supplied ready-for-use. Apply by brush, roller or airless spray. For a smoother finish on large areas use a short pile roller

DO NOT PAINT

IF THE TEMPERATURE IS BELOW 10°C OR ABOVE 35°C
IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 15%)
IF IT IS RAINING OR RAIN IS FORECAST
BEFORE 9H00 AND AFTER 16H00 IN THE WINTER



**FIRED
EARTH™**

**B.DS.029
BW SERIES**

HEALTH & SAFETY

Keep paint away from children. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.