



TECHNICAL DATA SHEET

SANDSTONE



GENERAL DESCRIPTION:

Sandstone Paint is a smooth slightly gritty textured coating drying to an elegant natural matt finish. Sandstone Paint handles moisture well and is an effective and practical solution for damp areas and boundary walls.

USES:

For use on suitably prepared and primed interior and exterior surfaces.

FEATURES & BENEFITS:

- Lead free
- Water clean up
- Easy to apply
- Hide slight imperfections on the wall

TECHNICAL INFORMATION	
1. SANDSTONE	
PHYSICAL FORM	Non-flammable viscous liquid containing pigments and extenders. May have a slight ammonia odour
COLOUR	Selected standard colours
FINISH	Light textured
SPREADING RATE	Approximately 5 - 7 m ² per litre per application
POLYMER TYPE	Alkali-resistant acrylic copolymer latex
FILLERS	Non-toxic extenders
PIGMENTS	Weather and light resistant types only
DRYING PROPERTIES	Surface or touch-dry: within 1 hour
RECOATING TIME	4 hours depending on conditions during drying
FLASH POINT	Not flammable in liquid form
PACKAGING	5L & 20L
THINNING	No Thinning required
CLEANING	Equipment is readily cleaned using water provided the paint is still wet. Cured paint may be removed using lacquer thinners or commercially available brush cleaners
APPLICATION METHOD	Supplied ready-for-use. Apply by brush or sheepskin roller suitable for water based ("PVA") paints (do not use rollers designed for enamels). Apply at the recommended spreading rate two coats of Sandstone Paint for optimal results. This paint should not be touched-up

DO NOT PAINT
IF THE TEMPERATURE IS BELOW 10°C OR ABOVE 35°C
IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 15%)
IF IT IS RAINING OR RAIN IS FORECAST
BEFORE 9H00 AND AFTER 16H00 IN THE WINTER



**FIRED
EARTH™**

**B.DS.005
BW SERIES**

HEALTH & SAFETY

Keep paint away from children. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.