



**B.DS.030
BW SERIES**

TECHNICAL DATA SHEET

WALLS & CEILINGS



GENERAL DESCRIPTION:

Fired Earth Walls & Ceilings Acrylic Paint is a high quality, high hiding washable Paint, formulated to achieve a perfect & even Matt white finish for walls & ceilings.

USES:

All interior and exterior masonry surfaces. May be used as a filler coating under PVA paints on interior walls over suitably prepared surfaces.

FEATURES & BENEFITS:

- Washable
- Stain resistant
- High hiding
- Lead free
- Low odour

TECHNICAL INFORMATION	
1. WALLS & CEILINGS	
PHYSICAL FORM	Non-flammable viscous liquid containing pigments and extenders. May have slight ammonia odour
COLOUR	White and standard colours
FINISH	Smooth matt
SPREADING RATE	Approximately 6 - 8 m ² / l per application
POLYMER TYPE	Alkali-resistant acrylic copolymer latex
FILLERS	Non-toxic pigments and extenders
PIGMENTS	Weather and light resistant types only
DRYING PROPERTIES	Surface or touch-dry: within 1 hour
RECOATING TIME	2 - 4h depending on conditions and film build
FLASH POINT	Not flammable in liquid form
PACKAGING	5L, 10L & 20L
THINNING	Not recommended, but if required to reduce viscosity add a minimum quantity of WATER. Excessive dilution degrades the quality of the product
CLEANING	Do not allow the product to dry on equipment. Equipment is readily cleaned using (Some detergent may be added to water to facilitate clean up)
APPLICATION METHOD	Supplied ready-for-use. Apply using good roller designed for PVA paint products

DO NOT PAINT
IF THE TEMPERATURE IS BELOW 10°C OR ABOVE 35°C
IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 15%)
IF IT IS RAINING OR RAIN IS FORECAST
BEFORE 9H00 AND AFTER 16H00 IN THE WINTER



**FIRED
EARTH™**

**B.DS.030
BW SERIES**

HEALTH & SAFETY

Keep paint away from children. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.