

B.DS.067 BW SERIES

TECHNICAL DATA SHEET

WALLS & WOOD



GENERAL DESCRIPTION:

Fired Earth Wall & Wood paint is a fragranced decorative matt acrylic for interior & exterior wood and wall surfaces.

USES:

Designed to fade and distress naturally, for walls, wood furniture and effects. Use it for a an even wash, distressed, textured or smooth contemporary matt finish. Use in old houses without damp proofing so walls can breathe.

FEATURES & BENEFITS:

- Lead Free
- Non-Toxic
- Easy to apply
- Can be applied to multiple surfaces
- Water Clean up

TECHNICAL INFORMATION	
1. WALLS & WOOD	
PHYSICAL FORM	Non-flammable viscous liquid containing pigments and extenders. May have slight ammonia odour
COLOUR	White and standard colours
FINISH	Smooth and matt
SPREADING RATE	Approximately 8 - 12 m ² per litre per application
POLYMER TYPE	Alkali-resistant acrylic copolymer latex
FILLERS	Non-toxic extenders
PIGMENTS	Weather and light resistant types only
DRYING PROPERTIES	Surface or touch-dry: within 1 hour
RECOATING TIME	4 hours depending on conditions during drying
FLASH POINT	Non-flammable (water based product)
PACKAGING	2.5L
THINNING	Not recommended, but if required to reduce viscosity add a minimum quantity of WATER. Excessive dilution degrades the quality of the product. (NB: DO NOT add solvent-based thinners such as turpentine or lacquer thinners)
CLEANING	Equipment is readily cleaned using water provided the paint is still wet. Cured paint may be removed using lacquer thinners or commercially available brush cleaners
APPLICATION METHOD	Apply using a quality paint roller or brush for walls. For decorative paint effects use tools specially designed i.e. sheepskin roller, fine sponge or pattern rollers, round and or standard quality paint brushes, a lint free cloth, sand paper, sea wool sponges, etc.

DO NOT PAINT
IF THE TEMPERATURE IS BELOW 10°C OR ABOVE 35°C
IF THE SURFACE IS DAMP (MOISTURE READING ABOVE 15%)
IF IT IS RAINING OR RAIN IS FORECAST
BEFORE 9H00 AND AFTER 16H00 IN THE WINTER

Created by: Karlien Bekker

Date: 11/06/2018 Date: 11/06/2018



B.DS.067 BW SERIES

HEALTH & SAFETY

Keep paint away from children. Never smoke, drink or eat while painting. Wear protective overalls, gloves and goggles. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun.

DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.

Reviewed Approved by: Harshil Kansara

Created by: Karlien Bekker